



(11) Publication number: **0 446 510 A1**

(12) **EUROPEAN PATENT APPLICATION**

(21) Application number: 90302813.2

(51) Int. Cl.<sup>5</sup>: **C10L 1/22**

(22) Date of filing: 15.03.90

(43) Date of publication of application:  
18.09.91 Bulletin 91/38

(84) Designated Contracting States:  
**BE DE FR GB**

(71) Applicant: **TEXACO DEVELOPMENT CORPORATION**  
2000 Westchester Avenue  
White Plains, New York 10650(US)


(72) Inventor: **Nalesnik, Theodore Eugene**

5 half Moon Road Chelsea  
Park Ridge, Beacon, NY 12508(US)  
Inventor: **Herbstman, Sheldon**  
2 Ferndale Road  
New City, NY 10956(US)

(74) Representative: **Brock, Peter William et al**  
**URQUHART-DYKES & LORD** 91 Wimpole  
Street  
London W1M 8AH(GB)

(54) **Stable middle distillate fuel-oil compositions.**

(57) Middle distillate fuel oil compositions such as diesel fuel or heating oil can be rendered storage-stable by an aromatic polyamine succinimide of a copolymer/maleic anhydride graft having the formula.




wherein (CP) is a copolymer and R is

EP 0 446 510 A1

BEST AVAILABLE COPY

## EP 0 446 510 A1



where R and R are each aryl, alkylaryl, HN-Aryl, alkoxy or H and  $n = 0$  or 6.

## EP 0 446 510 A1

This invention relates to middle distillate fuels and, more particularly, to a storage stabilizing additive for a middle distillate fuel-heating oil composition.

In the manufacture and production of middle distillate fuels and oils there is the problem of increased cracking of poorer quality crude oils. As a result, the commercially available diesel fuels and heating oils are less storage stable. Accordingly, stability additives are commonly introduced to prevent sludge formation and/or color change. However, to date these additives have not been effective or practical as to storage stabilizing middle distillates.

Thus, an object of the present invention is to provide a means of stabilizing efficiently a middle distillate, e.g., diesel fuels and heating oil, in storage.

U.S. Patent 4,089,794 discloses a process for preparing a lubricating oil concentrate of a VI improver having sludge dispersing properties wherein the VI improver is an ethylene copolymer with a number average molecular weight ranging from about 5,000 to 250,000 dissolved in a mineral lubricating oil.


U.S. Patent 4,171,273 discloses a method of preparing fatty alkyl succinate ester and succinimide modified copolymers of ethylene and an alpha-olefin which are useful as shear stable viscosity index (VI) improvers, dispersants and pour point dispersants in lubricating oils.

U.S. Patent 4,698,169 discloses additives useful in lubricant compositions having superior dispersant and antioxidant activity. The additives are products made by reacting (a) an alkenyl succinic compound with (b) an arylamine and (c) an alkanolamine or a hindered alcohol and borated reaction products thereof which provide dispersant and antioxidant activity to lubricant compositions.


In providing the present fuel-oil composition, i.e., a stable middle distillate, a storage stabilizing agent is added to the middle distillate fuel-oil.

According to the present invention, the stable middle distillate fuel oil composition comprises:

- (a) a major portion of a middle distillate fuel-oil; and
- (b) a minor amount of, as a storage stabilizing additive, an aromatic polyamine succinimide of a copolymer and maleic anhydride graft of the formula



wherein (CP) is a copolymer and R is



where R' and R'' each are aryl, alkylaryl, HN-Aryl, alkoxy or H and n = 0 or 6.

The polymer or copolymer substrate employed in the novel additive of the invention may be prepared from ethylene and propylene or it may be prepared from ethylene and a higher olefin within the range of C<sub>3</sub> to C<sub>10</sub> alpha-monoolefins.

More complex polymer substrates, often designated as interpolymers, may be prepared using a third component. The third component generally used to prepare an interpolymer substrate is a polyene monomer selected from non-conjugated dienes and trienes. The non-conjugated diene component is one

## EP 0 446 510 A1

having from 5 to 14 carbon atoms in the chain. Preferably, the diene monomer is characterized by the presence of a vinyl group in its structure and can include cyclic and bi-cyclo compounds. Representative dienes include 1,4-hexadiene, 1,4-cyclohexadiene, dicyclopentadiene, 5-ethylidene-2-norbornene, 5-methylene-2-norbornene, 1,5-heptadiene and 1,6-octadiene. A mixture of more than one diene can be used in the preparation of the interpolmer. A preferred non-conjugated diene for preparing a terpolymer or interpolmer substrate is 1,4-hexadiene.

The triene component will have at least two non-conjugated double bonds and up to about 30 carbon atoms in the chain. Typical trienes useful in preparing the interpolmer of the invention are 1-isopropylidene-3a,4,7,7a-tetrahydroindene, 1-isopropylidenedicyclopentadiene, dehydro-iso-dicyclopentadiene and 2-(2-methylene-4-methyl-3-pentenyl)-[2.2.1] bicyclo-5-heptene.

In the formulas above of the aromatic polyamines, R includes those and their isomers set forth below in Table 1.

TABLE 1

Isomers of Polyamines

N-phenylphenylenediamine

N-phenylnaphthylenediamine

N-naphthylphenylenediamine

N-4-anilino-N'-phenylphenylenediamine

The polymerization reaction to form the polymer substrate is generally carried out in the presence of a catalyst in a solvent medium. The polymerization solvent may be any suitable inert organic solvent that is liquid under reaction conditions for solution polymerization of monoolefins which is generally conducted in the presence of Ziegler type catalyst. Examples of satisfactory hydrocarbon solvents include straight chain paraffins having from 5-8 carbon atoms, with hexane being preferred. Aromatic hydrocarbons, preferably aromatic hydrocarbon having a single benzene nucleus, such as benzene, toluene and the like; and saturated cyclic hydrocarbons having boiling point ranges approximating those of the straight chain paraffinic hydrocarbons and aromatic hydrocarbons described above, are particularly suitable. The solvent selected may be a mixture of one or more of the foregoing hydrocarbons. It is desirable that the solvent be free of substances that will interfere with Ziegler polymerization.

In a typical preparation of a polymer substrate, hexane is first introduced into a reactor and the temperature in the reactor is raised moderately to about 30° C. Dry propylene is fed to the reactor until the pressure reaches about 40-45 inches of mercury. The pressure is then increased to about 60 inches of mercury and dry ethylene and 5-ethylidene-2-norbornene are fed to the reactor. The monomer feeds are stopped and a mixture of aluminum sesquichloride and vanadium oxytrichloride are added to initiate the polymerization reaction. Completion of the polymerization reaction is evidenced by a drop in the pressure in the reactor.

Ethylene-propylene or higher alpha monoolefin copolymers may consist of from about 15 to 80 mole percent ethylene and from about 20 to 85 mole percent propylene or higher monoolefin with the preferred mole ratios being from about 25 to 75 mole percent ethylene and from about 25 to 75 mole percent of a (C<sub>3</sub> to C<sub>10</sub>) alpha monoolefin with the most preferred proportions being from 25 to 55 mole percent ethylene and 45 to 75 mole percent propylene.

Terpolymer variations of the foregoing polymers may contain from about 0.1 to 10 mole percent of a non-conjugated diene or triene.

The polymer substrate, that is the ethylene copolymer or terpolymer, is an oil-soluble substantially linear, rubbery material having an average molecular weight from about 5,000 to 500,000 with a preferred average molecular weight range of 25,000 to 250,000 and a most preferred range from about 50,000 to 150,000.

The terms polymer and copolymer are used generically to encompass ethylene copolymers, terpolymers or interpolymers. These materials may contain minor amounts of other olefinic monomers so long as their basic characteristics are not materially changed.

An ethylenically unsaturated carboxylic acid material is next grafted onto the prescribed polymer

## EP 0 446 510 B1

EXAMPLE IPROCEDURE (NPPDA)

- 5        1. Dissolve 70 g of MA-EP in 513 g of SNO-100 base oil at 160°C under N<sub>2</sub> blanket.  
        2. Stir 2 hours at 160°C under N<sub>2</sub>.  
        3. Add a solution of 2.0 g of N-phenylphenylenediamine dissolved in 13 gms of surfonic N-40 (ethoxylated alkyl phenol solvent) and react for 2 hours at 160°C under N<sub>2</sub> (low flow rate).  
        4. Cool and screen filter (100 mesh).  
 10       The results of the test are provided below in Table 2.

TABLE 2RESULTS OF POTENTIAL DEPOSIT TEST

<u>Middle Distillate</u>	<u>Results*</u>
Base fuel (H-Oil Diesel Fraction)	3 ck 3
Base fuel + 60 PTB ECA 8477**	1 ck 1.5
20 Base Fuel + 60 PTB NPPDA (Ex.1)	1.5 ck 1.5


\*       The higher the number the poorer the stability of the fuel.

\*\*      A commercially available dispersant/stabilizer for diesel fuel.

The test results of Table 1 above indicate that this additive stabilizes the diesel fuel against heat and light-temperature oxidation and it is equivalent in activity to a commercially available additive.

Claims

1. A stable middle distillate fuel-oil composition comprising:  
 35       (a) a major portion of a middle distillate fuel-oil; and  
        (b) a minor amount of a storage-stabilizing additive, characterized in that the additive is an aromatic polyamine succinimide of a copolymer/maleic anhydride graft having the formula



wherein (CP) is a copolymer and R is

## EP 0 446 510 A1

[EP: Ethylene Propylene copolymer number average Mol. Wt. 80,000) MA graft level on EP is approximately 1.5 wt. %]

EXAMPLE I

5

PROCEDURE (NPPDA)

1. Dissolve 70 g of MA-EP in 513 g of SNO-100 base oil at 160°C under N<sub>2</sub> blanket.
2. Stir 2 hours at 160°C under N<sub>2</sub>.
3. Add a solution of 2.0 g of N-phenylphenylenediamine dissolved in 13 gms of surfonic N-40 (ethoxylated alkyl phenol solvent) and react for 2 hours at 160°C under N<sub>2</sub> (low flow rate).
4. Cool and screen filter (100 mesh).

The results of the test are provided below in Table 2.

15

TABLE 2RESULTS OF POTENTIAL DEPOSIT TEST

<u>Middle Distillate</u>	<u>Results*</u>
Base fuel (H-Oil Diesel Fraction)	3 ck 3
Base fuel + 60 PTB ECA 8477**	1 ck 1.5
Base Fuel + 60 PTB NPPDA (Ex.1)	1.5 ck 1.5
* The higher the number the poorer the stability of the fuel.	
** A commercially available dispersant/stabilizer for diesel fuel.	

The test results of Table I above indicate that this additive stabilizes the diesel fuel against heat and light-temperature oxidation and it is equivalent in activity to a commercially available additive.


Claims

1. A stable middle distillate fuel-oil composition comprising:
  - (a) a major portion of a middle distillate fuel-oil; and
  - (b) a minor amount of a storage-stabilizing additive, characterized in that the additive is an aromatic polyamine succinimide of a copolymer/maleic anhydride graft having the formula

40

45


50



wherein (CP) is a copolymer and R is

55

## EP 0 446 510 A1



where R and R are each aryl, alkylaryl, HN-Aryl, alkoxy or H and n = 0 or 6.

2. A composition according to Claim 1 characterized in that the copolymer is an ethylene/(C -C ) alpha-  
15 monoolefin copolymer.
3. A composition according to Claim 1 or 2 characterized in that the copolymer has a number average  
molecular weight from 5,000 to 500,000.
- 20 4. A composition according to any one of Claims 1 characterized in that the oil is a diesel fuel/heating oil.
5. A composition according to any one of Claims 1 characterized in that the additive is derived from a  
polytertiary amine selected from all isomers of N-phenylphenylenediamine, N-phenylnaph-  
thylenediamine, N-naphthyl-phenylenediamine and N-4-anilino-N'-phenylphenylenediamine.  
25 6. A composition according to any one of Claims 1 to 5 characterized in that the additive is N-(4-  
anilinophenyl)succinimide bound to an ethylene/propylene copolymer.

30

35

40

45

50

55



European  
Patent Office

## EUROPEAN SEARCH REPORT

Application Number

EP 90 30 2813

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.5)
Y	EP-A-0 338 672 (TEXACO) * Claim 1; examples 1,2; page 8, lines 32-39 *	1-5	C 10 L 1/22
A	---	6	
Y	FR-A-1 473 696 (CHEVRON) * Whole document *	1-5	
A	---	6	
A	US-A-3 306 852 (HENDRICKSON) * Whole document *	1-6	
D,A	US-A-4 698 169 (ANDRESS et al.) * Whole document *	1,5	
D,A	US-A-4 089 794 (ENGEL et al.) * Whole document *	1-4	
D,A	US-A-4 171 273 (WALDBILLIG et al.) * Whole document *	1-4	
E	US-A-4 919 683 (NALESNIK et al.) * Whole document *	1-6	TECHNICAL FIELDS SEARCHED (Int. Cl.5)  C 10 L C 08 F
The present search report has been drawn up for all claims			
Place of search		Date of completion of search	Examiner
The Hague		02 August 90	DE LA MORINERIE B.M.
CATEGORY OF CITED DOCUMENTS X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background O: non-written disclosure P: Intermediate document T: theory or principle underlying the invention E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons &: member of the same patent family, corresponding document			



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**